

Disc Skimmer

VH DS Datasheet



Size of Disc	300 mm to 600 mm
No of Discs	dia 1 to 6
Oil Removal Capacity	Upto 100 lph
Drive	3 Phase, AC Motor
Drive Power	1/4 HP, 1/2 HP, 1 HP (Depending on Application)
Drive Make	CGL/KIRLOSKAR/SIEMENS/ REMI/MOTOVARIO/Equivalent

Temperatur of Operation	Upto 120 °C
MOC of Wiper	Teflon (PTFE)
MOC of Disc	Stainless Steel 304/316
MOC of Frame	Mild Steel Powder Coated/SS 304/SS 316
MOC of Oil collection tray	Mild Steel Powder Coated/SS 304/SS 316

NOTE :

- Please ensure minimum dipping depth of the disc as in the drawing to ensure effective skimming of oil.
- Please position the equipment in the collection tank where the disturbance / turbulence due to flow of water is absent.
- Please provide enough clearance at the bottom of the tank to ensure slit or burr or hard particles do not rub or cling to the surface since the disc and the wipers may get damaged.

**Magnetic
separators**

**Belt
Oil Skimmers**

**Tube
Oil Skimmers**

**Wika
PressureGauge**

**Disk
Oil Skimmers**

**Mini Vacuum
Systems**

**Floating
Funnel
Skimmers**

**Oil
Spill Response
Equipment**

**Floating
Drum Skimmers**

**Chain
Oil Skimmers**

**Floating
Disk Skimmers**

**Filter
Elements**

**Slotted Tube
Oil Skimmers**

**Simplex &
Duplex housing filters**

**Coalescer
Oil Water Separators**

**Grooved
Disk type Skimmers**

**Truck Mounted
Vacuum Systems**

**Mini
Oil Skimmers**

**Compact
Oil Skimmers**



**Buy
Single Disk Here**